



EKAMANT

EKA BLACK

EKA BLACK IS AN EXCELLENT PRODUCT FOR SPECIAL APPLICATIONS that is tough to sand. Such as; Hardwood, MDF, UV lacquer for floor products, cement fibreboard and stainless steel.

The product combines the capacity for high rates of material removal with the ability to present an excellent surface finish with even scratch pattern.

The Antistatex® bonding system provides a fully antistatic effect which reduces clogging of the product and minimizes dust load on the sanding surface.

TECHNICAL SPECIFICATION

| | |
|-------------------|--------------------------------|
| Backing: | E-. F-weight paper |
| Bonding: | Resin over resin |
| Treatment: | Fully Antistatic - Antistatex® |
| Grit: | Silicon Carbide |
| Coating: | Semi open |
| A-range: | 60 - 320 |
| B-range: | 40, 400 |
| Width: | 1370 mm, 1420 mm on request |

APPLICATIONS


Product for calibration, intermediate and finishing sanding of material that is tough to sand.

| | |
|------------------|------------------------------------|
| Wood: | Hard wood |
| Board: | MDF, Chipboard |
| Lacquer: | Hard UV-lacquer for flooring |
| Specials: | Cement fibreboard, Stainless Steel |

RECOMMENDED FORMS



Wide belt



Narrow belt