



## EKAMANT

# EKA 3001 N

EKA 3001 N IS DESIGNED FOR THOSE APPLICATIONS WHERE SURFACE QUALITY is crucial and more important than high stock removal rates. The silicon carbide grit in combination with a pliable E-weight paper contributes to an efficient lacquer sanding operation with fine scratch pattern.

EKA 3001 N is further treated with a new improved stearate coating which effectively reduces clogging problems and contributes to an improved surface finish.

The Antistatex® bonding system provides a fully antistatic effect which reduces clogging of the product and minimizes dust load on the sanding surface.

### TECHNICAL SPECIFICATION

|                   |  |
|-------------------|--|
| <b>Backing:</b>   | E-weight paper                                 |
| <b>Bonding:</b>   | Resin over resin                               |
| <b>Treatment:</b> | Fully Antistatic - Antistatex®, Stearate layer |
| <b>Grit:</b>      | Silicon Carbide                                |
| <b>Coating:</b>   | Semi open                                      |
| <b>A-range:</b>   | P240 - P800                                    |
| <b>B-range:</b>   | P180 - P220, P1000 - P1200                     |
| <b>Width:</b>     | 1370 mm, 1420 mm on request                    |

### APPLICATIONS


Lacquer sanding of hard surface.

**Lacquer:** NC, PU, PE and UV-lacquer

### RECOMMENDED FORMS



Wide belt



Narrow belt